




TECHNICAL CHARACTERISTICS














wineo


wineo 1000 to click

Permanently elastic flooring according to EN 16511
without the addition of chlorin, without plasticisers or solvents

	wood L	wood XL	stone L
Format	1295 x 195 mm	1507 x 246 mm	642 x 330.5 mm
Product thickness	5 mm	5 mm	5 mm
Weight	~ 8.7 kg/m ²	~ 9 kg/m ²	~ 8.9 kg/m ²
Profile connection	Fold-Down 	Fold-Down 	LocTec 
Planks / m² per box	8 / 2.02 m ²	6 / 2.22 m ²	10 / 2.12 m ²
Boxes / m² per pallet	56 / 113.12 m ²	48 / 106.56 m ²	52 / 110.24 m ²



Classification		Product composition
 Utilization class 23 EN ISO 10874	Domestic area with intensive usage	1 Top element PU-top layer with NatureSurface, decor und stabilisation
 Utilization class 32 EN ISO 10874	Commercial sector with average usage	
 R9 Anti slip category DIN 51130	R 9	2 Profile connection Fold-Down locking (wood) LocTec locking (stone)
 Resistance to staining EN 438-2	Group 1, 2 + 3: grade 5	
 Light fastness EN ISO 105-B02	Light fastness (method 2) ≥ 6	3 Base layer ecuran high-performance composite material
 Residual indentation EN ISO 24343-1	≤ 0.1 mm	
 Castor chair test EN 425	25000 revolutions no damage with rolls type W	4 Backing Integrated FleeceTEC-System for easy and comfortable installation
 Thermal resistance ISO 8302	0.01 (m ² K)/W	
 Impact sound reduction EN ISO 10140	~ 5 dB	 
 Dimension stability EN ISO 23999	≤ 0.15 %	
REACH	free from SVHC substances ≥ 0.1 %	
Disposal	<u>Private:</u> possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203	 www.blauer-engel.de/uz120



Relevant Information:

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperatur of 27 °C.
- Cleaning and care: See separate cleaning & care instruction.
- Technical subjects can be changed by Windmüller GmbH.