

CARE INSTRUCTIONS

for DISANO design floor

After installation of the floor, it may be necessary to thoroughly clean the floor with clean & green active, the parquet cleaner from Hamberger. Please follow the instructions given in the “Intensive care” section under “Damp cleaning”.

Basic care:

Dry cleaning:

- It is usually sufficient to dry-clean your DISANO design floor with a mop, brush or vacuum.

Damp cleaning:

- For protection of the DISANO surface a treatment is necessary. Your floor should be cleaned regularly depending on the wear and tear of the surface with clean & green natural diluted in water.
- Add half a dosage cap of clean & green natural to five litres of water. Then wipe the surface with a well-wrung, slightly damp cloth. Don't clean the floor surface too damp, always avoid letting water stand on the surface. By polishing the floor with a cloth afterwards, you can optimize the shine of your floor's surface.



Intensive care:

Damp cleaning:

- As the floor will be subject to high traffic, the floor surface will need to be deep-cleaned periodically, depending on dirt build-up. Please use clean & green active for deep cleaning.
- Add half a dosage cap of clean & green active to five litres of water. Then wipe the surface with a well-wrung, slightly damp cloth. The surface of the floor. Don't clean the floor too damp, always avoid letting water stand on the surface. If required, repeat the process.



Refreshing:

- To optically refresh the floor and improve durability, we recommend that you use clean & green aqua shield.
- Start by thoroughly cleaning the floor (dust-free). We recommend clean & green active for this job. clean & green aqua shield is applied undiluted with the “Wischwiesel” flat wet-mop. Evenly apply the clean & green aqua shield in overlapping lines with the Wischwiesel. The room temperature should be between 18° and 22°C with relative humidity of 45% to 65%. Coverage: about 30 ml/m² depends on the absorbing power of the surface) Wait about 2 hours before subjecting the floor to traffic and load. The application of clean & green aqua shield can lead to changes in the gloss level.



Useful tips:

Climatic conditions:

- In order to maintain the quality and beauty of the floor, but also for your own personal well being, an indoor climate of approx. 30% - 60% relative air humidity is ideal with a room temperature of approx. 20° C (68°F).
- To keep the air humidity constant, especially during the heating period, we recommend that you use an electric humidifier. This prevents the floor from drying out excessively.

Basic protection:

- In maintaining the appearance of your DISANO design floor it is always beneficial to use protective felt pads under chairs and table legs and doormats in entrances (to protect your parquet against moisture, dirt and sand).
- Chair castors and office roller chairs must comply with German Standard DIN 68 1 31. Use only lined rollers of type W (soft). A further recommendation is to use the polycarbonate mats that are available in HARO Shop. Steam cleaning machines are not suitable for cleaning parquet flooring.