



## PRODUCT DETAILS

Surface treatment	Silk lacquer
Dimensions	2423 x 200 x 15 mm
Weight per Package (kg)	23 kg
Area per Package (m²)	2.9 m²
Area per pallet (m²)	0 m²
Package info	Packages may contain start and stop boards.

## DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

## COLOUR CHANGE

Changes from pink hues to deeper reddish brown tones.

## FACTS

Design	3-strip
Grading	Calm
Range	Kährs Original
Collection	American Naturals Collection
Resandable	2-3 times
Natural/Stained	Natural
Brinell Value	3,6
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear Layer Thickness (mm)	3.5 mm
Core material	Pine/Spruce lamella
Thickness (mm)	15 mm
Installation method	Glue-down, Floating

## TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD

Other products in this collection



Walnut Georgia



Walnut Montreal



Walnut Hartford



Hard Maple Toronto



Cherry Savannah

CERTIFICATES



Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*