



PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Surface treatment	Matt lacquer	Design	1-strip	Moisture	EN13183	7%±2%
Dimensions	2266 x 187 x 15 mm	Grading	Lively	content		
Weight per Package (kg) 20 kg		Range	Kährs Original	Minimun Mean Density kg/m³ >500 kg/m³		>500 kg/m ³
Area per Package (m²)	2.5 m ²	Collection	Classic Nouveau Collection	Reaction To Fire	EN13501-1	Dfl-s1
Area per pallet (m²) Package info	114.3 m ² Packages may contain	Resandable	2-3 times	Formaldehyde Emission	EN717-1	E1
	start and stop boards.	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
		Brinell Value	3,7	Strength	EN1533	NPD
		Joint	Woodloc® 5S		2.1.333	
DETAIL DESCRIPTION		Floor heating	Yes	N/mm²		
		Warranty	30 years	Thermal Conductivity	EN12664	0,14 W/mK
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Wear-layer material	Hardwood	Thermal Resistance R-Value		.11 (m2K/W)
		Wear Layer Thickness (mm)	3.5 mm	Biological Durability	EN350-2	Class 1
		Core material	Pine/Spruce lamella	CARB2		Compliant
COLOUR CHANGE		Thickness (mm)	15 mm	Slipperiness	CEN/TS15676	NPD
Stained product - noticable color change over time.		Installation method	Floating, Glue-down			
		Surface Colour	White 0W			

Other products in this collection



CERTIFICATES

Oak Nouveau White











Oak Nouveau Snow







Oak Nouveau Black

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.