Technical Data Sheet



planeo click vinyl rigid with impact sound insulation

Country house decors

Dimension		
Length	1220 mm	
Width	178 mm	
Thickness	3,5 + 1 mm	
Structure		
Wear layer	0,2 mm	
Bevel	no Bevel	
Floo r finish		
UV Finish		
Co nnecti on		
Click system (2G-2G)		
Country of manufacture		
China		
Packaging		
1 package = 8 planks	1,737 m²	
1 pallet = 90 packages = 720 planks	156,330 m²	
Properties		
EU classification		
Eo elassification	EN685	21, 22, 23 und 31
Wear	EN685 EN649	21, 22, 23 und 31 T
Wear	EN649	т
Wear Fire protection Residual pressure Light fastness	EN649 EN13501-1	T B _{fl} -s1
Wear Fire protection Residual pressure	EN649 EN13501-1 EN433	T B _{fl} -s1 passed
Wear Fire protection Residual pressure Light fastness	EN649 EN13501-1 EN433 ISO105B02	T B _{fl} -s1 passed ≥ 6
Wear Fire protection Residual pressure Light fastness Chemical resistance	EN649 EN13501-1 EN433 ISO105B02 EN423	T B _{fI} -s1 passed ≥ 6 passed

Suitable for hot water underfloor heating in accordance with the standard specifications. Suitable for professional floating installation. Please follow our installation instructions for installation.

Status: February 2021; subject to change